



Revision Date: 05/22/2007

Issue date: 05/22/2007

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: Pipe Repair Kit
Product type: Epoxy stick
Company address:
Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

Item No. : 96321_EPOXY STICK
Region: United States
Contact Information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Talc 14807-96-6	30-60	2 mg/m ³ TWA particulate matter containing no asbestos and <1% crystalline silica	= 20 mppcf TWA	50 ppm
Iron 7439-89-6	10-30	None	None	None
Epichlorohydrin-4,4'-isopropylidene diphenol resin 25068-38-6	10-30	None	None	None
Soda lime borosilicate glass 65997-17-3	10-30	1 fiber/cm ³ TWA respirable fibers: length > 5 µm, aspect ratio equal to or greater than 3:1, as determined by the membrane filter method at 400-450X magnification (4-mm objective), using phase-contrast illumination. 5 mg/m ³ TWA inhalable fraction	0.1 mg/m ³ TWA	None
Polyether polymercaptan UNKNOWN	5-10	None	None	None
Silica, quartz 14808-60-7	5-10	0.025 mg/m ³ TWA respirable fraction	0.1mg/m ³ TWA (respirable)	None
Treated fumed silica 67762-90-7	1-5	10mg/m ³ Inhalable fraction, 3mg/m ³ Respirable fraction, TWA	5mg/m ³ Respirable dust, 15mg/m ³ Total dust	None
Phenol, 2,4,6-tris[(dimethylamino)methyl] 90-72-2	5-10	None	None	None

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW****HMIS:**

Physical state: Putty
Color: Black Metallic
Odor: Sulfur, Mercaptan

HEALTH: 1*
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See Section 8

Item No. : 96321_EPOXY STICK

Product name: Pipe Repair Kit

WARNING: MAY CAUSE ALLERGIC SKIN REACTION.
MAY CAUSE EYE AND SKIN IRRITATION.

Relevant routes of exposure: Skin contact, Eye contact, Ingestion

Potential Health Effects

Inhalation: Not a relevant route of exposure. Contains crystalline silica (quartz), which is classified as a possible carcinogen. However, the crystalline silica present in this product is encapsulated in the epoxy resin and will only be liberated if the product is sanded or abraded, and even then what is liberated will not be a pure crystalline silica. Appropriate precautions, however, should be taken if the product is sanded or abraded to prevent personnel from breathing the dust.

Skin contact: Irritating to skin. May cause allergic skin reaction.

Eye contact: Contact with eyes will cause irritation.

Ingestion: May cause gastrointestinal tract irritation if swallowed.

Existing conditions aggravated by exposure: None known

See Section 11 for additional toxicological information.

4. FIRST AID MEASURES

Inhalation: Remove to fresh air. If symptoms develop and persist, get medical attention.

Skin contact: Immediately flush skin with plenty of water (using soap, if available). Remove contaminated clothing and shoes. Wash clothing before reuse. Get medical attention.

Eye contact: Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.

Ingestion: Do not induce vomiting. Keep individual calm. Never give anything by mouth to an unconscious person. Obtain medical attention.

5. FIRE-FIGHTING MEASURES

Flash point: Not applicable

Autoignition temperature: Not applicable

Flammable/Explosive limits-lower %: Not applicable

Flammable/Explosive limits-upper %: Not applicable

Extinguishing media: Carbon dioxide (CO₂). Foam. Dry chemical. Water spray.

Special fire fighting procedures: Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear.

Unusual fire or explosion hazards: None

Hazardous combustion products: Aldehydes. Acids. Oxides of carbon. Oxides of nitrogen. Oxides of sulfur.

6. ACCIDENTAL RELEASE MEASURES

Environmental precautions: None known

Clean-up methods: Scrape up as much material as possible. Store in a closed container until ready for disposal.

7. HANDLING AND STORAGE

Handling:	Avoid contact with skin and eyes. Wash thoroughly after handling. Empty container precaution: Attention! This container can be hazardous when empty. Follow label cautions even after the container is empty since empty containers could retain product residues. Do not re-use empty containers for food, clothing, or products for human or animal consumption, or where skin contact can occur.
Storage:	For safe storage, store at or below 32°C (90°F). Keep in a cool, well ventilated area.
Incompatible products:	None.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	Use local exhaust ventilation if heated above 38°C (100°F) to maintain concentrations below occupational exposure limits.
Respiratory protection:	Not normally required. Use NIOSH approved respirator if there is potential to exceed exposure limit(s).
Skin protection:	Chemical resistant, impermeable gloves. Because a variety of protective gloves exist, consult manufacturer to determine the proper type for a specific operation.
Eye/face protection:	Chemical splash goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Putty
Color:	Black Metallic
Odor:	Sulfur, Mercaptan
Vapor pressure:	Not applicable
pH:	Not applicable
Boiling point/range:	Not available
Melting point/range:	Not applicable
Specific gravity:	2.18
Vapor density:	Not applicable
Evaporation rate:	Not applicable
Solubility in water:	Not available
Partition coefficient (n-octanol/water):	Not available
VOC content:	<1%

10. STABILITY AND REACTIVITY

Stability:	Stable.
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	Aldehydes. Oxides of carbon. Oxides of nitrogen. Oxides of sulfur. Acids.
Incompatibility:	None
Conditions to avoid:	None known.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Talc 14807-96-6	No	No	No
Iron 7439-89-6	No	No	No
Epichlorohydrin-4,4'-isopropylidene diphenol resin 25068-38-6	No	No	No
Soda lime borosilicate glass 65997-17-3	Suspect Carcinogen	Group 2B	Yes
Polyether polymercaptan UNKNOWN	No	No	No
Silica, quartz 14808-60-7	Known Carcinogen	Group 1	Yes
Treated fumed silica 67762-90-7	No	No	No
Phenol, 2,4,6- tris[(dimethylamino)methyl] 90-72-2	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Talc 14807-96-6	Some evidence of carcinogenicity, Lung, Irritant
Iron 7439-89-6	Eyes, Lung
Epichlorohydrin-4,4'-isopropylidene diphenol resin 25068-38-6	Allergen, Irritant
Soda lime borosilicate glass 65997-17-3	Allergen, Respiratory
Polyether polymercaptan UNKNOWN	No data
Silica, quartz 14808-60-7	Some evidence of carcinogenicity, Lung, Immune system
Treated fumed silica 67762-90-7	Irritant
Phenol, 2,4,6- tris[(dimethylamino)methyl] 90-72-2	Allergen, Irritant

12. ECOLOGICAL INFORMATION

Ecological information: Not applicable

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Dispose according to EPA and local governmental regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Unrestricted
Hazard class or division: None

Item No. : 96321_EPOXY STICK

Product name: Pipe Repair Kit

Identification number: None
Packing group: None

WaterTransportation (IMO/IMDG):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None
Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: None.

CERCLA/SARA Section 302 EHS: None.
CERCLA/SARA Section 311/312: Immediate Health Hazard, Delayed Health Hazard
CERCLA/SARA 313: None.

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: 2, 11, 15

Prepared by: Gary Pierson, Sr. Product Safety and Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.