

# YDPU2.E48762 - TUBING, EXTRUDED INSULATING - COMPONENT

## Tubing, Extruded Insulating - Component

See General Information for Tubing, Extruded Insulating - Component

### SUMITOMO ELECTRIC FINE POLYMER INC

E48762

1-950 ASASHIRO NISHI

KUMATORI-CHO

SENNAN-GUN, OSAKA 590-0458 JAPAN

Cat. No.	Max V rms	Max Oper Temp, °C	Color Recognized	Oil-resistance Class[a]	VW-1 Rated[b]
<b>Irradiated flexible heat shrinkable Polyolefin (PO) tubing</b>					
<b>705 or Sumitube FPAC</b>	600	125	All except clear	-	Yes
<b>717 or Sumitube NHR2</b>	600	125	Pink, Yellow, Blue, Green, Red, Gray, Black	-	Yes
<b>Not heat shrinkable irradiated Polyvinyl Chloride (PVC) tubing</b>					
<b>806</b>	300	105	All except clear	-	Yes
<b>807</b>	600	105	All except clear	-	Yes
<b>Irradiated heat shrinkable Polyvinyl Chloride (PVC) tubing</b>					
<b>808</b>	300	105	All except clear	-	Yes
<b>809</b>	600	105	All except clear	-	Yes
<b>Irradiated flexible heat shrinkable Polyolefin (PO) tubing</b>					
<b>810 or Sumitube F</b>	600	105	All except clear	-	Yes
<b>811 or Sumitube F2</b>	600	125	All except clear	-	Yes
<b>Not heat shrinkable Polyvinyl Chloride (PVC) tubing</b>					
<b>816, 837</b>	300	105	CL	-	Yes
<b>817, 834</b>	600	105	CL	-	Yes
<b>Heat shrinkable Polyvinyl Chloride (PVC) tubing</b>					

<b>818, 836</b>	300	105		CL	-	Yes
<b>819, 835</b>	600	105		CL	-	Yes
<b>Irradiated flexible heat shrinkable Polyolefin (PO) tubing</b>						
<b>820 or Sumitube F</b>	600	105		All except clear	-	Yes
<b>821 or Sumitube F2</b>	600	125		All except clear	-	Yes
<b>Irradiated heat shrinkable Polyvinyl Chloride (PVC) tubing</b>						
<b>822</b>	300	105		All except clear	-	Yes
<b>Heat shrinkable Polyvinyl Chloride (PVC) tubing</b>						
<b>823</b>	300	105		CL	-	Yes
<b>Irradiated flexible heat shrinkable Polyolefin (PO) tubing</b>						
<b>826 or Sumitube B2 (a) or Sumitube B2C (a)</b>	600	125		All except clear	-	Yes
<b>Irradiated semi-rigid heat shrinkable Polyolefin (SRPO) tubing</b>						
<b>846 or Sumitube B8</b>	600	125		All except clear	-	Yes
<b>Irradiated flexible heat shrinkable Polyolefin (PO) tubing</b>						
<b>915</b>	600	125		BK	-	Yes
<b>938 or Sumitube F(TZ)</b>	600	105		All except clear	-	Yes
<b>939 or Sumitube F(Z)</b>	600	105		All except clear	-	Yes
<b>940, Sumitube F2(Z) or Sumitube T82</b>	600	125		All except clear	-	Yes
<b>958 or SM12</b>	600	125		All except clear	-	Yes
<b>963 or SM23</b>	600	125		All except clear	-	Yes
<b>Irradiated semi-rigid heat shrinkable Polyolefin (SRPO) tubing</b>						
<b>967 or Sumitube FC3</b>	600	125		All except clear	-	Yes
<b>Irradiated flexible heat shrinkable Polyolefin (PO) tubing</b>						
<b>982 or B2(Z)</b>	600	125		All except clear	-	Yes
<b>B2(3XZ) or B2(Z)4X</b>	600	125		All except clear	-	Yes
<b>B35 (a)</b>	600	125		All except clear	-	Yes
<b>Flexible not heat shrinkable Polyolefin (PO) tubing</b>						
<b>Irraxtube NHR4 or 719</b>	300	125	Pink, Yellow, Blue, Green, Red, Gray, Black		-	Yes
<b>Irradiated flexible heat shrinkable Polyolefin (PO) tubing</b>						
<b>SM3-12, SM3-23</b>	600	125		All except clear	-	Yes
<b>Sumitube B20, B20(3X) or 978</b>	600	125		All except clear	-	No
<b>Sumitube F(T)</b>	600	105		All except clear	-	Yes

<b>Sumitube F22(Z)</b>	600	125	All except clear	-	No
<b>Sumitube F32</b>	600	125	All except clear	-	Yes
<b>Sumitube F32(Z)</b>	600	125	All except clear	-	Yes
<b>Sumitube F5</b>	600	125	All except clear	-	Yes
<b>Sumitube F5(Z)</b>	600	125	All except clear	-	Yes
<b>Flexible heat shrinkable Polyolefin (PO) tubing</b>					
<b>Sumitube HF2</b>	600	125	BK	-	Yes

[a] - Tubing is considered to comply with the optional Oil Resistance requirements only if authorized in the above table and marked "Oil Resistant" (or "Oil Res"), followed by the class (01, 02 or 03).

[b] - Tubing is considered to comply with the optional VW-1 flammability requirements only if authorized in the above table and if so marked.

(a) - May be followed by suffix 3X, Y/G, FLT or (3X)FLT.

Marking: Company name or tradename "E48762" , "IRRAX" , "SUMI-PAC" , "SUMITUBE" , catalog designation, inside diameter (before and after recovery for heat-shrinkable tubing), voltage rating, temperature rating in degrees celsius and date of manufacture (or traceable code) printed on tags attached to both ends of the tubing or printed on the shipping spool label or smallest unit container in which the product is packaged.

Last Updated on 2019-02-20

---

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"