

E32系列

传感器指南

光纤式

放大器分离型











放大器内置型

电源内置型

用途分类

外围设备

介绍

种类		形状（mm）★2	检测距离(mm)			标准检测物体 (最小检测物体) (mm) ★1	弯曲 半径 (mm)	特长	型号				
标准型	耐曲折	标准尺寸					φ1(φ0.005)	B R4	M4螺钉	E32-T11			
					900				φ3圆柱	E32-T12B			
					680				450(180)	平面形状	E32-T15XB		
		小型尺寸							φ0.5(φ0.005)	M3螺钉 (小型)	E32-T21		
					240						200	φ2圆柱 (小型)	E32-T221B
					110(45)						φ1.5圆柱 (小型)	E32-T22B	
					180						150	平面形状 (小型)	E32-T25XB
			85(35)										
	涂层			900		680	φ1(φ0.005)	U R4	M4螺钉 氟涂层	E32-T11U			
			450(180)										
特殊光束型	长距离／高功能			20,000★3		20,000★3	φ10	R25	内置大型透镜 M14螺钉	E32-T17L			
			10,000 (4,000)										
				4,000★4		4,000★4	φ4(φ0.1)	R1	M4螺钉	E32-TC200 + E39-F1			
				2,600 (1,500)					M4螺钉 柔软光纤	E32-T11R + E39-F1			
					4,000★4				3,700	B R4	M4螺钉 耐曲折	E32-T11 + E39-F1	
				2,400 (970)									
				4,000★4		3,400	R25	螺钉安装 侧视	E32-T14				
			2,250 (900)			M4螺钉			E32-T11L				
				1,700					1,330	φ3圆柱	E32-T12L		
				870 (350)									

*1. 最小检测物体是在标准模式下将检测距离和灵敏度设定到最佳状态下得到的值 (代表例)。

*2. (Free-cut) 是自由切割的单元。

*3. 光纤长度单侧为10m, 因此总长20,000mm。

*4. 光纤长度单侧为2m, 因此总长4,000mm。

E32系列

E3X-DA-S
/E3X-MDA

E3X-NA

E3X-ZA

E3X-DRT21-S