



Certification Record

CUSTOMER	CLASS	FILE
Sumitomo Electric Fine Polymer Inc. 1-950 Asashiro nishi, Kumatori-Cho Sennan-Gun Osaka 590-0458 Japan	9032-01 INSULATING DEVICES AND MATERIALS-Insulating Tubing and Sleeving	033298_0_000
Refer to Class Description for program details		

TO THE REQUIREMENTS OF CSA STANDARD C22.2 NO. 198.1-06:

Cat No	Voltage Rating (V)	Temp Rating (°C)	Size Fractional/US Size Metric (in)	Size Metric (mm)	Optional Flame (VW-1)	Notes
Not heat-shrinkable PVC tubing:						
IRRAX TUBE V2	300	105	24 to 1/0	0.30 to 7.5	YES	1
	600	105	5/16 to 1-1/16	0.30 to 26.0	YES	1
Semi-Rigid irradiated cross-linked heat-shrinkable polyolefin tubing:						
SUMITUBE FC3 or 967	600	125	3/64 to 4	1.0 to 124	-	1
SUMITUBE B8	600	125	3/64 to 4	1.0 to 124	Yes	1
Flexible heat-shrinkable PVC tubing:						
SUMITUBE V	600	105	3/64 to 4	1.0 to 124	Yes	1
SUMITUBE V or 819	600	105	3/64 to 2	1.0 to 50	Yes	2
Flexible irradiated cross-linked heat-shrinkable PVF2 tubing:						
SUMITUBE K or 852	600	150	3/64 to 4	1.0 to 124	Yes	2
Flexible Irradiated cross-linked heat-shrinkable polyolefin tubing with meltable liner:						
SUMITUBE 02F2 (Z) or 02F2 or 951	600	125	1/8 to 1	3.0 to 25	-	1
SUMITUBE 02B2, 02B2S or 841	600	125	1/8 to 1 1/2	3.0 to 38	-	1
SUMITUBE W3F2	600	125	1/8 to 1	3.0 to 25	-	1
SUMITUBE W3F2 (Z) or 950	600	125	1/8 to 1	3.0 to 25	-	1
SUMITUBE W3B2 or W3B2S	600	125	0.13 to 1.6	3.0 to 40	-	1
Flexible irradiated cross-linked heat-shrinkable polyolefin tubing:						
SUMITUBE F2	600	125	3/64 to 4	1.0 to 124	Yes	1

SUMITUBE F22 (Z)	600	125	3/64 to 4	1.0 to 124	Yes	1
SUMITUBE F2 (Z) or 940 or T82	600	125	3/64 to 2	1.0 to 50	Yes	1
SUMITUBE F4	150	125	3/64 to 4	1.0 to 124	Yes	1
SUMITUBE F4 (Z) or 942 or T84	150	125	3/64 to 2	1.0 to 50	Yes	1
SUMITUBE F5 or F5(Z)	600	125	3/64 to 2	1.0 to 50	Yes	1
SUMITUBE F32 or 705	600	125	3/64 to 4	1.0 to 124	Yes	1
Flexible heat-shrinkable polyolefin tubing:						
SUMITUBE B2	600	125	3/64 to 6	1.0 to 124	Yes	1
SUMITUBE B2 (3X)	600	125	3/64 to 6	1.0 to 124	Yes	1
SUMITUBE B2 (Y/G)	600	125	3/64 to 6	1.0 to 124	Yes	1
SUMIMARK SM12	600	125	3/64 to 2	1.0 to 50.0	Yes	1
SUMIMARK SM3-12	600	125	3/64-2	1.0 to 50.0	Yes	1
SUMIMARK SM23	600	125	3/64-2	1.0 to 50.0	Yes	1
SUMIMARK SM3-23	600	125	3/64-2	1.0 to 50.0	Yes	1

Notes:

1. In all colours except for clear and translucent.
2. In clear and translucent.

- Flexible, cross-linked, heat-shrinkable, polyolefin tubing:

Cat. No.	Voltage Rating (V)	Temp Rating (°C)	Size		Optional Flame (VW-1)	Notes
			Fractional/US (in)	Size Metric (mm)		
SUMITUBE F2	600	125	3/64 - 1	1.0 - 30.0	Yes	1
SUMITUBE F32	600	125	3/64 - 1	1.0 - 30.0	Yes	1
SUMITUBE F4	150	125	3/64 - 1	1.0 - 30.0	Yes	1
SUMITUBE FPAC	600	125	3/64 - 1	1.0 - 30.0	Yes	1
SUMITUBE 705	600	125	3/64 - 1	1.0 - 30.0	Yes	1
SUMITUBE F34	150	125	3/64 - 1	1.0 - 30.0	Yes	1
SUMITUBE F33	600	125	3/64-1	1.0 - 30.0	Yes	1

Note: In all colours except clear.

/lb