



Revision Date: 12/09/2003

Issue date: 04/15/2004

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: DEERE 5900 7OZ AE
Product type: Silicone
Company address:
Henkel Corporation
1001 Trout Brook Crossing
Rocky Hill, Connecticut 06067

Item number: 34548
Region: United States
Contact Information:
Telephone: 860.571.5100
Emergency telephone: 860.571.5100
Internet: www.loctite.com

2. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Hazardous components</u>	<u>%</u>	<u>ACGIH TLV</u>	<u>OSHA PEL</u>	<u>OTHER</u>
Reinforcing filler Proprietary	30-60	10 mg/m ³ TWA (particulate matter containing no asbestos and <1% crystalline silica)	15 mg/m ³ TWA (total dust) 5 mg/m ³ TWA (respirable fraction)	None
Oximino silane Proprietary	1-5	None	None	None
Methyl ethyl ketoxime 96-29-7	1-5	None	None	None
Carbon black 1333-86-4	1-5	3.5 mg/m ³ TWA	3.5 mg/m ³ TWA	None
Methanol 67-56-1	0-0.1	200 ppm TWA 250 ppm STEL (skin)	200 ppm TWA 260 mg/m ³ TWA	None

Non hazardous components
Silicone Resins 30-50%

Exposure to moisture during cure will release 0.1 - 0.9% methyl alcohol. Methyl ethyl ketoxime(MEKO) is formed during cure. This product will release up to 5% MEKO.

3. HAZARDS IDENTIFICATION**EMERGENCY OVERVIEW****HMIS:**

Physical state: Paste
Color: Black
Odor: Mild

HEALTH: 1
FLAMMABILITY: 1
PHYSICAL HAZARD: 0
Personal Protection: See Section 8

CAUTION: CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION

Relevant routes of exposure: Skin, inhalation, eyes, Ingestion

Potential Health Effects

Item number: 34548

Product name: DEERE 5900 7OZ AE

Vapors and mist irritate the respiratory tract and nasal passages. When heated to temperatures exceeding 300° F (150° C) in the presence of air, silicones may form formaldehyde vapors. Formaldehyde is a potential cancer hazard and a known skin and respiratory sensitizer. Vapors irritate the eyes, nose and throat. Safe handling conditions may be maintained by keeping formaldehyde vapor concentrations below the OSHA permissible limit. The silane is a skin and eye irritant and may cause skin burns. Overexposure may cause coma and respiratory failure. The low concentration makes such overexposure unlikely and minimizes its affect on health and safety.

May cause skin irritation with discomfort or rash.

Vapors may irritate eyes. Contact with eyes will cause irritation.

Moderately toxic by ingestion. Not expected under normal conditions of use.

Skin disorders.

4. FIRST AID MEASURES

Remove to fresh air. If discomfort persists seek medical attention.

Wipe off paste with paper towel or cloth. Wash with soap and water.

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Do not induce vomiting. Keep individual calm. Obtain medical attention.

Greater than 93°C (200°F) Tagliabue closed cup

Not available

Not applicable

Not applicable

Carbon dioxide (CO₂). Foam. Dry chemical.

Wear self contained breathing apparatus

None

Formaldehyde. Silica fume.

Do not flush into surface water or sanitary sewer system.

Scrape up as much material as possible. Maintain good ventilation for large spills. Store in a partly filled, closed container until disposal.

7. HANDLING AND STORAGE

Handling:	Avoid contact with eyes, skin and clothing. Avoid breathing vapor and mist. Wash thoroughly after handling. Do not wear contact lenses.
Storage:	Store in a dry area below 90° F Keep container closed.
Incompatible products:	Never allow product to get in contact with water during storage.

For information on product shelf life contact Henkel Customer Service at (800) 243-4874.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Engineering controls:	Use local exhaust ventilation to maintain airborne concentrations below established exposure limits.
Respiratory protection:	Use a NIOSH approved air-purifying respirator if the potential to exceed established exposure limits exists.
Skin protection:	Chemical resistant, impermeable gloves. Impervious clothing
Eye/face protection:	Safety goggles or safety glasses with side shields.

See Section 2 for exposure limits.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Paste
Color:	Black
Odor:	Mild
Vapor pressure:	<5 mmHg @20°C (68° F)
pH:	8
Boiling point/range:	Not applicable
Melting point/range:	Not available
Specific gravity:	1.31 at 20 deg. C
Vapor density:	Heavier than air
Evaporation rate:	Not available
Solubility in water:	Polymerizes in presence of water
Partition coefficient (n-octanol/water):	Not available
VOC content:	4.01%; 52.5 grams/liter

10. STABILITY AND REACTIVITY

Stability:	Stable.
Hazardous polymerization:	Will not occur.
Hazardous decomposition products:	Methyl ethyl ketoxime formed during cure
Incompatibility:	Polymerizes on contact with water
Conditions to avoid:	Moisture.

11. TOXICOLOGICAL INFORMATION

Carcinogen Status

Hazardous components	NTP Carcinogen	IARC Carcinogen	OSHA Carcinogen
Reinforcing filler Proprietary	No	No	No
Oximino silane Proprietary	No	No	No
Methyl ethyl ketoxime	No	No	No
Carbon black	No	Group 2B	No
Methanol	No	No	No

Literature Referenced Target Organ & Other Health Effects

Hazardous components	Health Effects/Target Organs
Reinforcing filler Proprietary	Nuisance dust
Oximino silane Proprietary	Allergen, Irritant
Methyl ethyl ketoxime	Allergen, Blood, Central nervous system, Eyes, Irritant, Some evidence of carcinogenicity
Carbon black	Respiratory, Some evidence of carcinogenicity
Methanol	Eyes, Heart, Irritant, Kidney, Liver, Metabolic, Nervous System, Reproductive

12. ECOLOGICAL INFORMATION

Ecological information:

No specific studies have been conducted by Henkel on the ecotoxicity or environmental fate of this material; however, commonly available data on the material indicate that uncontrolled releases to soil, groundwater, or surface waters could entail acute and/or chronic ecological effects, depending on the quantity and concentration of such releases. Releases of volatile components to the atmosphere are not believed to entail significant ecological consequences provided such releases are within the exposure levels set forth in this document. Accordingly, all appropriate measures should be taken to avoid uncontrolled releases to the environment, and any spills or other uncontrolled releases which may occur should be contained and cleaned up immediately in accordance with Section 6.

13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Cured rubber can be incinerated or landfilled following EPA and local regulations.

EPA hazardous waste number: Not a RCRA hazardous waste.

14. TRANSPORT INFORMATION

U.S. Department of Transportation Ground (49 CFR):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None

International Air Transportation (ICAO/IATA):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None
Exceptions: May Qualify as Consumer Commodity ID8000 For Aerosol Packages only (Not more than 500ml)

WaterTransportation (IMO/IMDG):

Proper shipping name: Unrestricted
Hazard class or division: None
Identification number: None
Packing group: None
Exceptions: None
Marine pollutant: None

15. REGULATORY INFORMATION

United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.
TSCA 12 (b) Export Notification: Methyl ethyl ketoxime (CAS# 96-29-7).

CERCLA/SARA Section 302 EHS: None.
CERCLA/SARA Section 311/312: None.
CERCLA/SARA 313: None.

California Proposition 65: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm. Toluene (CAS# 108-88-3). <1 ppm. Propylene oxide (CAS# 75-56-9) Trace. Ethylene Oxide (CAS# 75-21-8) Trace. 1,4-Dioxane (CAS# 123-91-1). Trace.

Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Domestic Substances List.
WHMIS hazard class: D.2.A, D.2.B

16. OTHER INFORMATION

This material safety data sheet contains changes from the previous version in sections: New Material Safety Data Sheet format.

Prepared by: Lou Fabrizio, Senior Health & Regulatory Affairs Specialist

DISCLAIMER: The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation does not assume responsibility for any results obtained by persons over whose methods Henkel Corporation has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any of Henkel Corporation's products. In light of the foregoing, Henkel Corporation specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation further disclaims any liability for consequential or incidental damages of any kind, including lost profits.