

Technical specs

PARA-ARAMIDE PREOX ALUMINISED HEAT AND SPLASH RESISTANT JACKET

VESTE19A-C

Size:

Single

Colour:

Aluminium-coloured



Description :

Para-aramide Preox jacket with aluminized Reflespace film 520 g/m². Aluminized fabric stand-up collar. DELTA design. Straight sleeve bottom. Snap and adhesive band closure. Lined with fire-retardant Proban® cotton.

Materials:

Aluminised preox para-aramid 520g/m²

Instructions for use:

Protective jacket for industrial workers exposed to heat. Protects against brief contacts with flame and against convective heat and radiant heat, and against molten aluminium and molten cast iron splash. For optimum protection, this jacket must be worn closed, with the closed aluminized PREOX hood (reference CAGOULE19A-C), the PREOX aluminised gaiters (reference GUETRE19A-C), the gloves TERK 400 (reference TERK400A-C) and the aluminised PREOX pants (reference PANTA19A-C).

Limits to use:

It is not recommended to use this clothing beyond its performance levels, nor for protections which do not come within its scope of application.

Instructions for storage:

Store in the original packaging, in dark, dry conditions.

Instructions for cleaning / maintenance:

Clean with soap and scrub brush or sponge. Dirty clothing can reduce the level of protection. Clothing performance depends on good condition after use. If the aluminized side shows wear, or if there is the presence of cracks or tears, the clothing must be replaced.

Performances :

Complies with the requirements in European directive 89/686, particularly with respect to ergonomics, harmlessness, comfort, ventilation, flexibility and to the European standards:

- EN340:1993 (general requirements)
- EN531: 1995 (Protection clothing for workers in industries exposed to heat): A B2 C2 D3 E3
- * EN532 (Limited flame propagation): Classe A
- * EN367 (Convective heat): Level B2 (6s<HTI24<13s)
- * EN366 (Radiant heat): Level C2 (30s<T2<91s)
- * EN373 (Molten aluminium splash): Level D3 (351g)
- * EN373 (Molten cast iron splash): Level E3 (201g)

Production of this item is subjected to the CE quality assurance system (article 11B of the directive 89/686/CEE) with inspection by the accredited control bureau: n°0333 - ASSOCIATION FRANÇAISE POUR L'ASSURANCE QUALITE (A.F.A.Q.), Avenue Aristide Briand, 116 - B.P.40, 92224 Bagneux Cedex - France

Technical specs

VESTE19A-C

- **EN531:1995** Protective clothing for the workers of industry exposed to heat.



A : Limited propagation of flame

B2 : Convective heat (between B0 and B5)

C2 : Radiant heat (between C0 and C4)

D3 : Molten aluminium splash (between D0 and D3, X = Not tested)

E3 : Molten cast iron splash (between E0 and E3, X = Not tested)