

Storage Cabinets for Flammable and Combustible Liquids

These cabinets are for the storage of flammable liquids in containers not exceeding 55 gallon (210 L) capacity. Total cabinet capacity is limited to 120 gallon (455 L); max storage of liquids in drums is limited to vertical orientation of drums to preclude self-dispensing. Cabinets are constructed of at least 18 gauge steel with a 1 1/2 in. (38 mm) air space all around between the inner and outer surfaces including door openings, or from at least 1 in. (25 mm) plywood. Doors have a lockable 3 point latching system and the door sill is at least 2 in. (51 mm) above bottom of cabinet. The cabinets are equipped with a 2 in. (51 mm) deep, leak-tight, sump or pan. Each cabinet has also passed a 10 minute exposure fire test according to a time-temperature relationship described in ASTM E152 in which internal temperature (at top center) cannot exceed 325°F (163°C).

Manual Close with Inset Handle

Manual Close with inset handle: 89140, 89250, 89310, 89460, 89610, 872200, 891200, 891300, 891302, 891500, 891700, 891702, 892200, 892211, 892300, 893000, 893002, 893010, 893011, 893300, 893302, 893400, 894500, 894502, 894510, 894511, 895400, 896000, 896002, 896010, 896011, 896200, 896260, 899000, 899002, 8930053, 8930076, 8945053, 8945076, 8960076, 8962053, 8962253, 8990076, 871200, 873000, 874500, 876000, 879000.

Company Name:	Justrite Mfg Co
Company Address:	3921 Dewitt Ave, Mattoon, Illinois 62938, USA
Company Website:	http://www.justritemfg.com
Listing Country:	United States of America
Capacity (Gallons):	
Capacity (Liters):	
Certification Type:	FM Approved