

E32系列

传感器指南

光纤式

放大器分离型

放大器内置型

电源内置型

用途分类

外围设备

介绍
















E32系列

E3X-DA-S
/E3X-MDA

E3X-NA

E3X-ZA

E3X-DRT21-S

种类	形状 (mm) *3	检测距离(mm) *1	(最小检测物体) (mm) *2	弯曲 半径 (mm)	特长	型号			
标准型	标准尺寸	 (Free-cut) M6	500 300 200(90)	(φ0.005)	R25	M6螺钉	E32-DC200		
		 (Free-cut) φ3	400 230 160(70)			φ3圆柱	E32-D12		
		 (Free-cut) 15x10x3	500			平面形状	E32-D15X		
		 (Free-cut) 内为B4型 90(40) 套管部不可弯曲 M6 φ2.5	500 300 200(90)			M6螺钉 带套管	E32-DC200B E32-DC200B4		
		 (Free-cut) φ6	200 110 80(36)			φ6圆柱 侧视	E32-D14L		
		 (Free-cut) 15x10x3	170			平面形状 侧视	E32-D15Y		
		 (Free-cut) 15x10x3	100 65(30)			平面形状 平视	E32-D15Z		
	小型尺寸	 (Free-cut) M4				R10	M4螺钉 (小型)	E32-D211	
		 (Free-cut) M3					M3螺钉 (小型)	E32-DC200E	
		 (Free-cut) φ3					130 80 50(22)	φ3圆柱 (小型)	E32-D22
		 (Free-cut) 12x8x2					平面形状 (小型)	E32-D25X	
		 (Free-cut) 内为F4型 90(40) 套管部不可弯曲R5 M3 φ1.2					M3螺钉 (小型) 带套管	E32-DC200F E32-DC200F4	
		 (Free-cut) φ2					50 30 20(8)	φ2圆柱 (小型) 侧视	E32-D24
		 (Free-cut) 12x8x2					35 20	平面形状 (小型) 侧视	E32-D25Y
 (Free-cut) 12x8x2	12(6)	平面形状 (小型) 平视	E32-D25Z						

*1. 检测距离是使用白画纸时的值。

*2. 最小检测物体是在标准模式下将检测距离和灵敏度设定到最佳状态下得到的值 (代表例)。

*3. (Free-cut) 是可自由切割的单元。